Author Index

Allotta, B.	Probabilistic analysis of braking performance in railways	149–166
Aparicio, J. L.	MEDES: contact wire wear measuring system used by the Spanish National Railway (RENFE)	167–176
Ayasse, J. B.	A unique design method for wheel profiles by considering the contact angle function	25–30
Barmada, S.	Wavelet multiresolution analysis for monitoring the occurrence of arcing on overhead electrified railways	177–188
Borromeo, S.	MEDES: contact wire wear measuring system used by the Spanish National Railway (RENFE)	167–176
Boudali, H.	A Simulink simulation framework of a MagLev model	227–236
Bugarín, M. R.	Madrid tram–train feasibility study conclusions	1–10
Chen, Y. C.	The effect of proximity of a rail end in elastic–plastic contact between a wheel and a rail	189–202
Chollet, H.	A unique design method for wheel profiles by considering the contact angle function	25–30
Cook, P. W.	Fatigue design of rubber springs used in rail vehicle suspensions	237–240
Craighead, I. A.	An investigation into the mechanical damping characteristics of catenary contact wires and their effect on aerodynamic galloping instability	63–72
da Silva, L. F. M.	Fatigue crack growth of rails for railways	89–98
de Castro, P. M. S. T.	Fatigue crack growth of rails for railways	89–98
de Oliveira, F. M. F.	Fatigue crack growth of rails for railways	89–98
Dhanasekar, M.	A three-dimensional model for the lateral and vertical dynamics of wagon–track systems	31–45
Diedrichs, B.	On computational fluid dynamics modelling of crosswind effects for high-speed rolling stock	203–226
Dwyer-Joyce, R. S.	Disc machine study of contact isolation during railway track sanding	11–24
Fernandez, J.	An investigation into the mechanical damping characteristics of catenary contact wires and their effect on aerodynamic galloping instability	63–72
Giras, T. C.	A Simulink simulation framework of a MagLev model	227–236
Goodman, C. J.	Modelling passenger flows at a transport interchange using Petri nets	125–134
Hayakawa, T.	Bioremediation of polychlorinated biphenyl contaminated sludge and ballast	285–290
Hillmansen, S.	The application of fuel cell technology to rail transport operations	291–298
Janic, M.	High-speed rail and air passenger transport: a comparison of the operational environmental performance	259–269
Johansson, A.	Out-of-round railway wheels—wheel–rail contact forces and track response derived from field tests and numerical simulations	135–146
Ju, S.-H.	Three-dimensional analyses of two high-speed trains crossing on a bridge	99–110
Kari, L.	Audible-frequency stiffness of a primary suspension isolator on a high-speed tilting bogie	47–62
Kim, M.-S.	Numerical simulation of unsteady compressible flows induced by a high-speed train passing through a tunnel	111–124
Kim, S.-W.	Correlation of ride comfort evaluation methods for railway vehicles	73–88
Kim, T.-Y.	Numerical simulation of unsteady compressible flows induced by a high-speed train passing through a tunnel	111–124
Kim, Y.-G.	Correlation of ride comfort evaluation methods for railway vehicles	73–88
Kimbara, K.	Bioremediation of polychlorinated biphenyl contaminated sludge and ballast	285–290
Kwon, H.-B.	Correlation of ride comfort evaluation methods for railway vehicles	73–88
Kwon, H.-B.	Numerical simulation of unsteady compressible flows induced by a high-speed train passing through a tunnel	111-124
Kyotani, T.	Bioremediation of polychlorinated biphenyl contaminated sludge and ballast	285–290
Landi, A.	Wavelet multiresolution analysis for monitoring the occurrence of arcing on overhead electrified railways	177–188
Lee, D.-H.	Numerical simulation of unsteady compressible flows induced by a high-speed train passing through a tunnel	111–124
Lewis, J.	Disc machine study of contact isolation during railway track sanding	11–24
Lewis, R.	Disc machine study of contact isolation during railway track sanding	11–24
Lin, H.-T.	Three-dimensional analyses of two high-speed trains crossing on a bridge	99–110
Luo, R. K	Fatigue design of rubber springs used in rail vehicle suspensions	237–240
Malvezzi, M.	Probabilistic analysis of braking performance in railways	149–166
Martínez, P. M.	MEDES: contact wire wear measuring system used by the Spanish National Railway (RENFE)	167–176
Matsuoka, S.	Recyclability of stainless steel railway vehicles	279–284
Miyauchi, T.	Application of lifecycle assessment to Shinkansen vehicles and cross ties in Japan	271–278
Mortel, W. J.	Fatigue design of rubber springs used in rail vehicle suspensions	237–240

© IMechE 2003

Nielsen, J. C. O.	Out-of-round railway wheels—wheel–rail contact forces and track response derived from field tests and numerical simulations	135–146
Novales, M.	Madrid tram–train feasibility study conclusions	1–10
Orro, A.	Madrid tram–train feasibility study conclusions	1–10
Papi, M.	Wavelet multiresolution analysis for monitoring the occurrence of arcing on overhead electrified railways	177–188
Park, C.-K.	Correlation of ride comfort evaluation methods for railway vehicles	73–88
Park, T.-W.	Correlation of ride comfort evaluation methods for railway vehicles	73–88
Pratt, I.	A unique design method for wheel profiles by considering the contact angle function	25–30
Presciani, P.	Probabilistic analysis of braking performance in railways	149–166
Roach, D.	A three-dimensional model for the lateral and vertical dynamics of wagon–track systems	31–45
Roberts, C.	Modelling passenger flows at a transport interchange using Petri nets	125–134
Sani, L.	Wavelet multiresolution analysis for monitoring the occurrence of arcing on overhead electrified railways	177–188
Scanlon, T. J.	An investigation into the mechanical damping characteristics of catenary contact wires and their effect on aerodynamic galloping instability	63–72
Schulte-Werning, B.	Research of European railway operators to reduce the environmental impact of high-speed trains	249–257
Shen, G.	A unique design method for wheel profiles by considering the contact angle function	25–30
Shimura, M.	Bioremediation of polychlorinated biphenyl contaminated sludge and ballast	285–290
Smith, R. A.	Railways: how they may contribute to a sustainable future	243–248
Stewardson, D. J.	Fatigue crack growth of rails for railways	89–98
Stickland, M. T.	An investigation into the mechanical damping characteristics of catenary contact wires and their effect on aerodynamic galloping instability	63–72
Sun, Y. Q.	A three-dimensional model for the lateral and vertical dynamics of wagon–track railways	31–45
Takagi, R.	Modelling passenger flows at a transport interchange using Petri nets	125–134
Toni, P.	Probabilistic analysis of braking performance in railways	149–166
Tsujimura, T.	Application of lifecycle assessment to Shinkansen vehicles and cross ties in Japan	271–278
Ueda, H.	Application of lifecycle assessment to Shinkansen vehicles and cross ties in Japan	271–278
Ushiogi, T.	Bioremediation of polychlorinated biphenyl contaminated sludge and ballast	285–290
Williams, R. D.	A Simulink simulation framework of a MagLev model	227–236
Wu, W. X.	Fatigue design of rubber springs used in rail vehicle suspensions	237–240

© IMechE 2003